

Application No. 10/709,626  
Reply to Office Action of December 5, 2005

Docket No.: 12051-00001-US

### AMENDMENTS TO THE CLAIMS

1. (currently amended) A hand-held ballistic shield, comprising:  
a shield having a front face and a reverse face and formed of a ballistic material;  
a viewing window through the shield;  
a handle associated with the shield for carrying the shield or holding the shield in front of at least a portion of a user's body; and  
a firearm mounted to the shield and dischargeably operable from the reverse face when so mounted, wherein said firearm is mounted for discharge in a direction at an angle outwardly from the front face of the shield.
2. (original) The ballistic shield of claim 1, wherein the firearm is selected from the group consisting of: taser guns, pistols, revolvers, gas discharge firearms.
3. (original) The ballistic shield of claim 1, wherein the ballistic material is selected from the group consisting of: boron carbide, silicon carbide, silicon nitride, aluminum oxide, alumina ceramic, titanium diboride, reinforced fiberglass composite, reinforced fiber and polymer resin composite, and mixtures of such materials.
4. (original) The ballistic shield of claim 1, wherein the viewing window is formed from a material selected from the group consisting of: bullet proof glass and polycarbonate polymer.
5. (original) The ballistic shield of claim 1, wherein the handle is a forearm cuff.
6. (original) The ballistic shield of claim 1, wherein the firearm is a taser gun, and further comprising a battery mounted to the shield for charging the taser gun.

Application No. 10/709,626  
Reply to Office Action of December 5, 2005

Docket No.: 12051-00001-US

7. (original) The ballistic shield of claim 1, further comprising a disabling sensor to disable the firearm in response to a predetermined signal or a predetermined absence of a signal.
8. (original) The ballistic shield of claim 1, wherein the firearm is mounted so that it discharges in a direction substantially perpendicular to the front face of the shield.
9. (canceled)
10. (original) The ballistic shield of claim 1, further comprising a second firearm mounted to the shield.
11. (original) The ballistic shield of claim 10, wherein the second firearm is mounted so that it discharges in a direction substantially parallel to the rear face of the shield.
12. (original) The ballistic shield of claim 1, further comprising a second weapon mounted to the rear face of the shield.
13. (original) The ballistic shield of claim 1, further comprising one or more communications accessories mounted to the shield.
14. (original) The ballistic shield of claim 13, wherein the communications accessories are selected from the group consisting of: radio, camera, digital camera, video camera, cellular phone, cellular video, audio speaker, megaphone, homing signaling device, and global positioning transponder.
15. (original) The ballistic shield of claim 1, further comprising one or more mirrors associated with the viewing window to extend the field of vision through said viewing window.
16. (original) The ballistic shield of claim 1, further comprising one or more light sources mounted to the shield.

Application No. 10/709,626  
Reply to Office Action of December 5, 2005

Docket No.: 12051-00001-US

17. (original) The ballistic shield of claim 1, wherein shield is employable and the firearm is dischargeable with a single arm operation.

18. (currently amended) A portable ballistic shield, comprising:

- a shield having a front face and a reverse face and formed of a ballistic material;
- a viewing window through the shield;
- a handle associated with the shield for carrying the shield or holding the shield in front of a user's body;
- a first firearm mounted to the shield and dischargeably operable from the reverse face when so mounted;
- a second firearm mounted to the shield and dischargeably operable when so mounted, wherein said second firearm is mounted so as to discharge in a direction that is different from a discharge direction of said first firearm;
- one or more light sources mounted to the shield; and
- a disabling sensor to disable the firearms in response to a predetermined signal or a predetermined absence of a signal.